

Zavíně na klávesnici v Linuxu - Ubuntu

Růžná

Napsal/a: Kozoroh

Vloženo : 9. 12. 2009 18:17:02

Chybě vím na české klávesnici v linuxu zavíně (nechce se vím její psát kombinací kláves např. pravé Alt + v) ?

Růžná klávesy v linuxu lze změnit následujícím postupem.

Zeditujeme soubor /usr/share/X11/xkb/symbols/cz (v pádě cz klávesnice)

Nalezněte nějakou klávesu, kterou nepoužijete a místo ní napište **at** (ang. zavíně)

Já jsem si její dal vlevo od klávesy y, kde bylo zprůměrované lomítko.

Partial default alphanumeric_keys

xkb_symbols "basic" {

```
// This layout conforms to a new cz compromise standard designed
// to satisfy most unix, windows and mac users.
// 2001 by Kamil Toman
```

include "latin"

name[Group1]= "Czechia";

```
key { [ semicolon, dead_abovering, grave, asciitilde ] };
key { [ plus, 1, exclam, dead_tilde ] };
key { [ ecaron, 2, at, dead_caron ] };
key { [ scaron, 3, numbersign, dead_circumflex ] };
key { [ ccaron, 4, dollar, dead_breve ] };
key { [ rcaron, 5, percent, dead_abovering ] };
key { [ zcaron, 6, asciicircum, dead_ogonek ] };
key { [ yacute, 7, ampersand, dead_grave ] };
key { [ aacute, 8, asterisk, dead_abovedot ] };
key { [ iacute, 9, braceleft, dead_acute ] };
key { [ eacute, 0, braceright, dead_doubleacute ] };
key { [ equal, percent, NoSymbol, dead_diaeresis ] };
key { [ dead_acute, dead_caron, dead_macron, dead_cedilla ] };
```

```
key { [ q, Q, backslash, NoSymbol ] };
key { [ w, W, bar, NoSymbol ] };
key { [ e, E, EuroSign, NoSymbol ] };
```

```

key { [ r, R, NoSymbol, NoSymbol ] };
key { [ t, T, NoSymbol, NoSymbol ] };
key { [ z, Z, NoSymbol, NoSymbol ] };
key { [ u, U, NoSymbol, NoSymbol ] };
key { [ i, I, NoSymbol, NoSymbol ] };
key { [ o, O, NoSymbol, NoSymbol ] };
key { [ p, P, NoSymbol, NoSymbol ] };

key { [ uacute, slash, bracketleft, division ] };
key { [ parenright, parenleft, bracketright, multiply ] };

key { [ a, A, asciitilde, NoSymbol ] };
key { [ s, S, dstroke, NoSymbol ] };
key { [ d, D, Dstroke, NoSymbol ] };
key { [ f, F, bracketleft, NoSymbol ] };
key { [ g, G, bracketright, NoSymbol ] };
key { [ h, H, grave, NoSymbol ] };
key { [ j, J, apostrophe, NoSymbol ] };
key { [ k, K, lstroke, NoSymbol ] };
key { [ l, L, Lstroke, NoSymbol ] };

key { [ uring, quotedbl, dollar, NoSymbol ] };
key { [ section, exclam, apostrophe, ssharp ] };
key { [ EuroSign, dead_diaeresis, NoSymbol, NoSymbol ] };
key { [ dead_diaeresis, apostrophe, backslash, bar ] };

key { [ at, bar, slash, NoSymbol ] };
key { [ y, Y, degree, NoSymbol ] };
key { [ x, X, numbersign, Nosymbol ] };
key { [ c, C, ampersand, NoSymbol ] };
key { [ v, V, at, NoSymbol ] };
key { [ b, B, braceleft, NoSymbol ] };
key { [ n, N, braceright, NoSymbol ] };
key { [ m, M, asciicircum, NoSymbol ] };
key { [ comma, question, less, NoSymbol ] };
key { [ period, colon, greater, NoSymbol ] };
key { [ minus, underscore, asterisk, NoSymbol ] };

key { [ space, space, nobreakspace, nobreakspace ] };

include "level3(ralt_switch)"
};
partial default alphanumeric_keys
xkb_symbols "basic" {

    // This layout conforms to a new cz compromise standard designed
    // to satisfy most unix, windows and mac users.
    // 2001 by Kamil Toman

```

include "latin"

name[Group1]= "Czechia";

```
key { [ semicolon, dead_abovering, grave, asciitilde ] };
key { [ plus, 1, exclam, dead_tilde ] };
key { [ ecaron, 2, at, dead_caron ] };
key { [ scaron, 3, numbersign, dead_circumflex ] };
key { [ ccaron, 4, dollar, dead_breve ] };
key { [ rcaron, 5, percent, dead_abovering ] };
key { [ zcaron, 6, asciicircum, dead_ogonek ] };
key { [ yacute, 7, ampersand, dead_grave ] };
key { [ aacute, 8, asterisk, dead_abovedot ] };
key { [ iacute, 9, braceleft, dead_acute ] };
key { [ eacute, 0, braceright, dead_doubleacute ] };
key { [ equal, percent, NoSymbol, dead_diaeresis ] };
key { [ dead_acute, dead_caron, dead_macron, dead_cedilla ] };
```

```
key { [ q, Q, backslash, NoSymbol ] };
key { [ w, W, bar, NoSymbol ] };
key { [ e, E, EuroSign, NoSymbol ] };
key { [ r, R, NoSymbol, NoSymbol ] };
key { [ t, T, NoSymbol, NoSymbol ] };
key { [ z, Z, NoSymbol, NoSymbol ] };
key { [ u, U, NoSymbol, NoSymbol ] };
key { [ i, I, NoSymbol, NoSymbol ] };
key { [ o, O, NoSymbol, NoSymbol ] };
key { [ p, P, NoSymbol, NoSymbol ] };
```

```
key { [ uacute, slash, bracketleft, division ] };
key { [ parenright, parenleft, bracketright, multiply ] };
```

```
key { [ a, A, asciitilde, NoSymbol ] };
key { [ s, S, dstroke, NoSymbol ] };
key { [ d, D, Dstroke, NoSymbol ] };
key { [ f, F, bracketleft, NoSymbol ] };
key { [ g, G, bracketright, NoSymbol ] };
key { [ h, H, grave, NoSymbol ] };
key { [ j, J, apostrophe, NoSymbol ] };
key { [ k, K, lstroke, NoSymbol ] };
key { [ l, L, Lstroke, NoSymbol ] };
```

```
key { [ uring, quotedbl, dollar, NoSymbol ] };
key { [ section, exclam, apostrophe, ssharp ] };
key { [ EuroSign, dead_diaeresis, NoSymbol, NoSymbol ] };
key { [ dead_diaeresis, apostrophe, backslash, bar ] };
```

```
key { [ at, bar, slash, NoSymbol ] };
key { [ y, Y, degree, NoSymbol ] };
```

```

key { [ x, X, numbersign, NoSymbol ] };
key { [ c, C, ampersand, NoSymbol ] };
key { [ v, V, at, NoSymbol ] };
key { [ b, B, braceleft, NoSymbol ] };
key { [ n, N, braceright, NoSymbol ] };
key { [ m, M, asciicircum, NoSymbol ] };
key { [ comma, question, less, NoSymbol ] };
key { [ period, colon, greater, NoSymbol ] };
key { [ minus, underscore, asterisk, NoSymbol ] };

key { [ space, space, nobreakspace, nobreakspace ] };

include "level3(ralt_switch)"
};

```

Restartujeme KDE např. odhlášením a přihlášením.

Při editaci souboru pozor na to, abyste nedělali v řádku znaků, mezer nebo tabulátorů, protože to pak problém.

V přepínači, můžete jako CZ klávesnici vybranou jinou než "basic", tak je pravdy nutno provést v přepínači mutaci nebo v souboru.

PS: editaci nutno provést pod root příkazy. Např. z Krusaderu v rootu.